



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 350 706 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
08.10.2003 Bulletin 2003/41

(51) Int Cl.7: **B62D 1/12**

(21) Application number: **03007201.1**

(22) Date of filing: **29.03.2003**

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PT RO SE SI SK TR**
Designated Extension States:
AL LT LV MK

(30) Priority: **01.04.2002 JP 2002099170**

(71) Applicant: **KOYO SEIKO CO., LTD.**
Osaka 542-0081 (JP)

(72) Inventors:
• **Higashi, Masayasu**
Chuo-ku, Osaka 542-0081 (JP)
• **Maeda, Shingo**
Chuo-ku, Osaka 542-0081 (JP)

- **Segawa, Masaya**
Chuo-ku, Osaka 542-0081 (JP)
- **Kimura, Shuuji**
Chuo-ku, Osaka 542-0081 (JP)
- **Hayama, Ryouhei**
Chuo-ku, Osaka 542-0081 (JP)
- **Kada, Tomoyasu**
Chuo-ku, Osaka 542-0081 (JP)


(74) Representative: **Selting, Günther, Dipl.-Ing. et al**
Patentanwälte
von Kreisler, Selting, Werner
Postfach 10 22 41
50462 Köln (DE)

(54) Steering apparatus for vehicle

(57) The steering means 1 is constructed by supporting a center portion of a rectangle-plate-shaped operation plate 11 at one end of a supporting shaft 10 projected from the front face of a dashboard D so as to freely swing in right and left directions. A steering apparatus for a vehicle having the steering means 1 detects the swing direction and the swing angle of the operation

plate 11 with a steering angle sensor 14 provided at a support portion and moves a steering mechanism in the detected direction in accordance with the detected angle so as to steer the vehicle. With this structure, a load in steering can be decreased and tiredness in driving can be reduced. Furthermore, such a steering apparatus can realize steering means which physically handicapped drivers can operate easily.

FIG. 1A



Description

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0001] The present invention relates to a steering apparatus for a vehicle, which is used for steering the vehicle in accordance with steering operations performed on steering means by a driver.

2. Description of Related Art

[0002] A vehicle is steered by transmitting steering operations performed on steering means by a driver in the passenger's room to a steering mechanism disposed outside the passenger's room so as to turn tire wheels for steering (right and left front wheels, in general) by movement of the steering mechanism.

[0003] Recently proposed as one of steering apparatuses for achieving such steering in Japanese Patent Application Laid-Open No. 10-218000 (1998) by the present applicant is a steering apparatus of separate type, or of what is called steer-by-wire type, wherein steering means in the passenger's room is provided mechanically separately from a steering mechanism at the outside of the passenger's room. In the steering apparatus of separate type, an actuator for steering, which is attached to a part of the steering mechanism, is moved on the basis of detection results of an operation direction and an operation amount of the steering means, realizing steering according to steering operations performed on the steering means.

[0004] The steering apparatus of separate type has advantages that correspondence between the steering amount of the steering means and the movement amount of the actuator, or what is called a steering transfer ratio, can be set freely without mechanical limit and that steering characteristics can be controlled and changed flexibly in response to a running state such as a vehicle speed, a swing speed and existence of change in speed. It should be noted that an electric motor is widely used as the actuator on account of the easiness to control and change the steering characteristics.

[0005] The aforementioned steering apparatus of separate type has advantages that no limit exists in the structure and arrangement of the steering means and that suitable steering means to be used can be selected. However, many of the conventionally proposed steering apparatuses of separate type, including the steering apparatus disclosed in Japanese Patent Application Laid-Open No. 10-218000, employ steering means (which is hereinafter referred to as steering-wheel-shaped steering means) formed in imitation of a steering wheel which is generally used in a steering apparatus of non-separate type.

[0006] In a steering apparatus of non-separate type, a ring-shaped steering wheel is attached to one end of

a column shaft mechanically connected with a steering mechanism and a turn of the column shaft according to a turning operation of the steering wheel is mechanically transmitted to the steering mechanism, realizing steering by movement of the steering mechanism according to the transmission. It should be noted that a steering apparatus configured as a power steering apparatus provided with an actuator aiming at reduction of driver's load is in practical use, the actuator being driven to apply steer-assisting force to a steering mechanism on the basis of a detection result of the steering torque which is applied to the column shaft by steering operations performed on the steering wheel.

[0007] The steering-wheel-shaped steering means employed in the steering apparatus of separate type, which is provided with a ring member fixed on one end of a turning shaft mechanically separated from the steering mechanism, detects the turning direction and turning amount of the turning shaft due to the turning operation of the ring member and moves the actuator for steering attached to the steering mechanism on the basis of the detection result. It should be noted that a reaction force motor is attached to the middle portion of the turning shaft as reaction force applying means. Turning force of the reaction force motor is transmitted to the turning shaft via reduction means to perform the turning operation of the ring member against the turning force, allowing the driver to feel reaction force against steering which is practically applied to the steering mechanism.

[0008] The steering apparatus of separate type provided with the aforementioned steering means has an advantage of providing the same feeling in steering as the steering apparatus of non-separate type, however, has a problem that the load put on the driver by repeated steering is large and occurrence of tiredness after driving for a long time is unavoidable since steering of such steering means requires a large operation amount. Furthermore, there arises another problem that a physically handicapped driver meets difficulties in steering of such a steering apparatus.

BRIEF SUMMARY OF THE INVENTION

[0009] The present invention has been made with the aim of solving the above problems, and it is an object thereof to provide a steering apparatus for a vehicle which is provided with steering means capable of decreasing a load in steering, reducing tiredness in driving and realizing easy steering operations for physically handicapped drivers, taking advantage of a steering apparatus of separate type that no limit exists in the structure and arrangement of the steering means.

[0010] A steering apparatus for a vehicle according to the present invention comprises steering means mechanically separated from a steering mechanism of the vehicle and moves the steering mechanism on the basis of detection results of operation direction and an operation amount of the steering means. In this steering ap-

paratus for a vehicle, the steering means includes a plate-shaped or rod-shaped operation member which is supported so as to freely swing with a center portion thereof being fixed and detecting means for detecting a swing direction and a swing angle of the operation member respectively as the operation direction and the operation amount.

[0011] In this steering apparatus for a vehicle, the steering means may further include a first shaft projected from a part of the body of the vehicle, a second shaft, which is coupled with the first shaft so as to be shifted with regard to the first shaft, for supporting the operation member and a displacement detector for detecting a displacement direction and a displacement amount of the second shaft. In this case, the steering mechanism operates on the basis of the swing direction and the swing angle of the operation member detected by the detecting means and the displacement direction and the displacement amount of the second shaft detected by the displacement detector.

[0012] Moreover, in this steering apparatus for a vehicle, the steering means may further include a supporting shaft, which is projected from a part of the body of the vehicle, for supporting the operation member so as to be rotated on a center axis thereof and a rotation detector for detecting a rotation direction and a rotation amount of the operation member. In this case, the steering mechanism operates on the basis of the swing direction and the swing angle of the operation member detected by the detecting means and the rotation direction and the rotation amount of the operation member detected by the rotation detector.

[0013] With this steering apparatus for a vehicle, steering is achieved by detecting a swing direction and a swing angle of a plate-shaped or rod-shaped operation member which is operated to swing with a center portion thereof being fixed and moving the steering mechanism in the detected direction in accordance with the detected swing angle. Since a swinging operation of the operation member is easy and requires a small operation amount, a load in steering can be decreased and tiredness in driving can be reduced. Furthermore, such a steering apparatus can provide physically handicapped drivers with opportunities of driving. The operation member may be disposed in a suitable position in the passenger's room, such as on the front face of the dashboard, on the upper face of the armrest, at the lower portion of the seat or at the space around driver's feet, allowing the driver to operate the member in a comfortable position.

[0014] In another steering apparatus for a vehicle according to the present invention, the steering means includes an operation member which is supported so as to be freely displaced along a linear displacement pathway and detecting means for detecting a displacement direction and a displacement amount of the operation member respectively as the operation direction and the operation amount.

[0015] With this steering apparatus for a vehicle, steering is achieved by detecting a displacement direction and a displacement amount of the operation member which is displaced linearly and moving the steering mechanism in the detected direction in accordance with the detected displacement amount. Since a displacement operation of the operation member is easy and requires a small operation amount, a load in steering can be decreased and tiredness in driving can be reduced. Furthermore, such a steering apparatus can provide physically handicapped drivers with opportunities of driving. The operation member may be disposed in a suitable position in the passenger's room, such as on the front face of the dashboard or on the upper face of the armrest, allowing the driver to operate the member in a comfortable position.

[0016] In another steering apparatus for a vehicle according to the present invention, the steering means includes a pair of grip members which are arranged in correspondence to operation directions respectively, and detecting means for detecting strengths of grip forces applied to the grip members as operation amounts in operation directions corresponding to the respective grip members.

[0017] With this steering apparatus for a vehicle, steering is achieved by detecting strengths of grip forces applied to a pair of grip members which are arranged in correspondence to right and left operation directions respectively, and moving the steering mechanism in directions corresponding to the respective grip members in accordance with the strengths of the detected grip forces. Since gripping of the grip members is easy and requires a small operation amount, a load in steering can be decreased and tiredness in driving can be reduced. Furthermore, such a steering apparatus can provide physically handicapped drivers with opportunities of driving. The grip members may be disposed in suitable positions in the passenger's room, allowing the driver to grip and operate the member in a comfortable position.

[0018] In another steering apparatus for a vehicle according to the present invention, the steering means includes a dial which is supported so as to be rotated on a center axis thereof and detecting means for detecting a rotation direction and a rotation amount of the dial respectively as the operation direction and the operation amount.

[0019] With this steering apparatus for a vehicle, steering is achieved by detecting a rotation direction and a rotation amount of the dial which is rotated on a center axis thereof and moving the steering mechanism in the detected direction in accordance with the detected rotation amount. Since a rotation operation of the dial is easy and requires a small operation amount, a load in steering can be decreased and tiredness in driving can be reduced. Furthermore, such a steering apparatus can provide physically handicapped drivers with opportunities of driving. The dial may be disposed in a suitable position in the passenger's room, such as on a part of

the steering wheel or on the upper face of the armrest, allowing the driver to steer the vehicle in a comfortable position.

[0020] In another steering apparatus for a vehicle according to the present invention, the steering means includes: an operation member formed of a strip-shaped member having end portions supported separately and a U-shaped operation portion between the supported end portions; and detecting means for detecting forces, which are applied to the supported end portions by a pulling operation of the operation member, as operation amounts in directions corresponding to the respective supported end portions.

[0021] With this steering apparatus for a vehicle, steering is achieved by detecting forces which are applied to the supported end portions by pulling the U-shaped operation member formed by supporting end portions of a strip-shaped member at a pair of support portions corresponding to the right and left operation directions respectively, and moving the steering mechanism in directions corresponding to the respective supported end portions in accordance with the strengths of the detected forces. Since the pulling operation of the operation member is easy and requires a small operation amount, a load in steering can be decreased and tiredness in driving can be reduced.

[0022] The above and further objects and features of the invention will more fully be apparent from the following detailed description with accompanying drawings.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0023]

FIGS. 1A and 1B are views for showing the first embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention;

FIGS. 2A and 2B are views for showing the second embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention;

FIGS. 3A and 3B are views for showing the third embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention;

FIGS. 4A and 4B are views for showing the fourth embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention;

FIG. 5 is a view for showing the fifth embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention;

FIG. 6 is a view for showing the sixth embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention;

FIG. 7 is a view for showing the seventh embodi-

ment of steering means provided in a steering apparatus for a vehicle according to the present invention;

FIGS. 8A and 8B are views for showing the eighth embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention;

FIGS. 9A and 9B are views for showing the ninth embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention;

FIGS. 10A and 10B are views for showing the tenth embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention;

FIG. 11 is a view for showing the eleventh embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention;

FIG. 12 is a view for showing the twelfth embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention;

FIG. 13 is a view for showing the thirteenth embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention;

FIG. 14 is a view for showing the fourteenth embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention; and

FIG. 15 is an explanatory view for showing a state at the time of steering, which can be realized by a vehicle including one of the steering means shown in FIG. 1A through FIG. 14.

DETAILED DESCRIPTION OF THE INVENTION

[0024] The following description will explain the present invention in detail with reference to the drawings illustrating some embodiments thereof. FIG. 1A is an external perspective view for showing the first embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention. FIG. 1B is a sectional side view of the steering means.

[0025] The steering means 1 shown in these figures comprises: a supporting shaft 10 which is projected from a part of the car body, such as the front face of a dashboard D, toward a driver (who is not illustrated in the figures) sitting on the driver's seat in the passenger's room; and a rectangle-plate-shaped operation plate (operation member) 11 supported on one end of the supporting shaft 10. As shown in FIG. 1B, a supporting pin 12 penetrates one end portion of the supporting shaft 10 upward and downward so as to cross the supporting shaft 10 approximately at a right angle. A supporting bracket 13 is provided at an approximately center portion of one face of the operation plate 11. The support

of the operation plate 11 on the end of the supporting shaft 10 is achieved by rotatably supporting the supporting bracket 13 at the supporting pin 12 with the longitudinal direction of the operation plate 11 being directed right and left.

[0026] The operation plate 11 supported in this manner can freely swing around the axis of the supporting pin 12. A driver who has a seat facing the operation plate 11 and grips right and left edge portions of the operation plate 11 can perform a swinging operation in right and left directions by pushing and pulling the gripped portions. FIG. 1A illustrates in two dotted dash lines a state where the operation plate 11 is made swing by a pushing operation on the right side thereof.

[0027] As shown in FIG. 1B, a steering angle sensor 14 and reaction force applying means 15 are attached to a support portion of such an operation plate 11. The aforementioned pushing and pulling operations make the operation plate 11 swing under resistance applied to the support portion by the reaction force applying means 15. The steering angle sensor 14 detects the swing angle as well as the swing direction.

[0028] The steering angle sensor 14 is constructed by, for example, attaching a rotational angle detector such as a rotary encoder at the support portion of the operation plate 11 so as to detect a relative angular displacement between the supporting pin 12 and the supporting bracket 13. The reaction force applying means 15 is composed of, for example, a motor attached so as to apply turning force to the support portion of the operation plate 11 and a neutralization spring for applying spring force to the support portion so as to bias the operation plate 11 to a neutral position. Here, the neutral position is a position where the operation plate 11 crosses the supporting shaft 10 approximately at a right angle and does not swing in any direction as illustrated in full lines in FIG. 1A. A driver who performs a swinging operation of the operation plate 11 from the neutral position feels the turning force of the motor and the spring force of the neutralization spring as reaction force against steering.

[0029] A steering mechanism, which is not illustrated in the figures, disposed mechanically separately from the steering means 1 detects the operation direction of the motor provided in the reaction force applying means 15 and a reaction force applied from the road surface according to the operation. The motor is controllably driven on the basis of the detection results. The swing direction and the swing angle of the operation plate 11 detected by the steering angle sensor 14 are handled as the direction and the amount of the operation of the operation means 1 performed for steering and are used for controlling an operation of a steering actuator, which is not illustrated in the figures, disposed in the steering mechanism. The control may be performed in control procedures which are disclosed in Japanese Patent Application Laid-Open No. 10-218000 by the present applicant as control procedures for a steering apparatus

of separate type having steering-wheel-shaped steering means.

[0030] In a vehicle comprising the steering means 1 constructed as described above, a driver who sits on the driver's seat can steer the vehicle by gripping the both edges of the operation plate 11 positioned at the front and operating the operation plate 11 to swing in right and left directions. In comparison with a turning operation of a steering wheel generally used as steering means, the swinging operation of such an operation plate 11 is easy and requires a small operation amount, and thereby a load in steering can be decreased and tiredness in driving for a long time can be reduced. Furthermore, such a steering apparatus can provide physically handicapped drivers with opportunities of driving.

[0031] It should be noted that, although the above explanation has described a case where the steering means 1 shown in FIGS. 1A and 1B is solely provided, the steering means 1 may be provided for assisting the steering-wheel-shaped steering means and used, for example, only for steering at a relatively small angle during a drive on open roads or the like.

[0032] FIG. 2A is an external perspective view for showing the second embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention. FIG. 2B is a sectional side view of the steering means. The steering means 1 comprises, similarly to the steering means 1 shown in FIGS. 1A and 1B, a supporting shaft 10 which is projected from the front face of a dashboard D and an operation plate 11 which is supported on one end of the supporting shaft 10 at the approximately center portion thereof so as to swing right and left. The steering means 1 achieves steering by detecting, with a steering angle sensor 14, the swing direction and the swing angle of the operation plate 11 under reaction force applied by the reaction force applying means 15 and moving the steering actuator attached to the steering mechanism on the basis of the detection result. Since the support structure of the operation plate 11 and the structures and operations of the steering angle sensor 14 and the reaction force applying means 15 are the same as those of the first embodiment shown in FIGS. 1A and 1B, detailed description thereof is omitted.

[0033] The feature of this embodiment lies in that the supporting shaft 10 is composed of a hollow lower shaft 10a and an upper shaft 10b for supporting the operation plate 11 which are coupled with each other in a telescopic manner so that a driver gripping the operation plate 11 can perform swinging operations of the operation plate 11 in right and left directions as well as pushing and pulling operations of the operation plate 11 in an axial direction of the supporting shaft 10 associated with telescopic motion of the lower shaft 10a and the upper shaft 10b. The amount of each operation is detected by a displacement sensor 16 which is interposed between the lower shaft 10a and the upper shaft 10b as schematically shown in FIG. 2B. FIG. 2A illustrates in two

dotted dash rules a state where the operation plate 11 is pulled out, illustrates in full lines a state where the operation plate 11 is pushed in and illustrates in one dotted dash rules a state where the operation plate 11 is made swing by a pushing operation at the right side at the pushed-in position.

[0034] The detection result of the displacement sensor 16 can be used, for example, for controlling the correspondence between the amount of swinging operation of the operation plate 11 and the movement amount of the steering actuator, or what is called a transfer ratio of steering. In this case, a wide variety of steering forms can be provided including an example wherein a large scale steering is performed by a combination of a push-in operation and a swinging operation of the operation plate 11 while a small scale steering is performed by a combination of a pull-out operation and a swinging operation.

[0035] Moreover, the detection result of the displacement sensor 16 can be used, for example, for controlling increase and decrease of running speed by using the push-in operation as an acceleration operation and the pull-out operation as a brake operation. In this case, approximately the whole of the operations for driving a vehicle can be provided by the combination of swinging operations and pushing and pulling operations of the operation plate 11.

[0036] FIG. 3A is an external perspective view for showing the third embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention. FIG. 3B is a sectional side view of the steering means. The steering means 1 shown in these figures comprises, similarly to the steering means 1 shown in FIGS. 1A and 1B, a supporting shaft 10 which is projected from the front face of a dashboard D and an operation plate 11 which is supported on one end of the supporting shaft 10 at the approximately center portion thereof so as to be swing in right and left directions. The steering means 1 achieves steering by detecting, with a steering angle sensor 14, the swing direction and the swing angle of the operation plate 11 under reaction force applied by the reaction force applying means 15 and moving the steering actuator attached to the steering mechanism on the basis of the detection result. Since the support structure of the operation plate 11 on the end of the supporting shaft 10 and the structures and operations of the steering angle sensor 14 and the reaction force applying means 15 are the same as those of the first embodiment shown in FIGS. 1A and 1B, detailed description thereof is omitted.

[0037] The feature of this embodiment lies in that the supporting shaft 10 is supported so as to freely turn on an axis thereof so that a driver gripping the operation plate 11 can perform turning operations of the operation plate 11 with the supporting shaft 10 in addition to the swinging operations of the operation plate 11 in right and left directions. FIG. 3A illustrates in two dotted dash rules a state where the operation plate 11 is made swing

by a pushing operation at the right side thereof while FIG. 3B illustrates in two dotted dash rules a state where a turning operation is performed on the operation plate 11.

[0038] A rotational angle sensor 17 attached to the middle portion of the supporting shaft 10 detects the amount of such a turning operation of the operation plate 11 as well as the turning direction. The detection result can be used for controlling an operation of the steering actuator, similarly to the detection result of the steering angle sensor 14, so that a large scale steering is performed by a turning operation and a small scale steering is performed by a swinging operation. Moreover, similarly to the second embodiment, the detection result of the rotational angle sensor 17 can be used for controlling the correspondence between the amount of swinging operation of the operation plate 11 and the movement amount of the steering actuator, or what is called a transfer ratio of steering, so that a large scale steering is performed by a combination of a turning operation in the same direction and a turning operation and a small scale steering is performed only by a swinging operation. In these manners, a wide variety of steering forms can be provided.

[0039] FIG. 4A is an external perspective view for showing the fourth embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention. FIG. 4B is a sectional side view taken along the line B-B in FIG. 4A.

[0040] The steering means 1 shown in these figures comprises a supporting shaft 10 which stands approximately vertically on the upper face of an armrest A provided on the inner face of a side door which is not illustrated in the figures and a rectangle-plate-shaped operation plate (operation member) 11 which is supported on one end of the supporting shaft 10. As shown in FIG. 4B, a supporting pin 12 penetrates one end portion of the supporting shaft 10 backward and forward so as to cross the supporting shaft 10 approximately at a right angle. A supporting bracket 13 is provided on an approximately center portion of one face of the operation plate 11. The support of the operation plate 11 on the end of the supporting shaft 10 is achieved by rotatably supporting the supporting bracket 13 at the supporting pin 12. The operation plate 11 supported in this manner can be operated to swing around the axis of the supporting pin 12 in right and left directions as indicated by arrows in FIG. 4A.

[0041] As shown in FIG. 4B, a steering angle sensor 14 and reaction force applying means 15 are attached at a support portion of the operation plate 11. The aforementioned swinging operations of the operation plate 11 are performed under resistance applied to the support portion by the reaction force applying means 15. The steering angle sensor 14 detects the swing angle as well as the swing direction. The structures and operations of the steering angle sensor 14 and the reaction force applying means 15 are the same as those of the first em-

bodiment shown in FIGS. 1A and 1B, and the detailed description thereof is omitted. It should be noted that FIG. 4A illustrates only the position of the supporting shaft 10 at the rear face of the operation plate 11 and the supporting pin 12, supporting bracket 13, steering angle sensor 14 and reaction force applying means 15 are omitted in this figure.

[0042] In a vehicle provided with the steering means 1 constructed in this manner, a driver who sits on the driver's seat can perform a desired steering by operating the operation plate 11 to swing right and left with his arm laid on the armrest A and with his palm put on the upper face of the operation plate 11. Since such a swinging operation of the operation plate 11 is easy and requires a small operation amount in comparison with a turning operation of a steering-wheel-shaped steering means generally used, a load in steering can be decreased and tiredness in driving can be reduced. Moreover, such a steering apparatus can provide physically handicapped drivers with opportunities of driving. Further more, with this embodiment wherein the driver sitting on the driver's seat can steer the vehicle in a comfortable position with his arm laid on the armrest A as mentioned above, tiredness in driving can be further reduced.

[0043] FIG. 5 is a view for showing the fifth embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention. The steering means 1 shown in the figure comprises a supporting shaft 10 which is positioned under driver's feet and stands approximately vertically from a floor F of the passenger's room and an operation plate 11 which is supported on one end of the supporting shaft 10 at the center portion thereof so as to swing in right and left directions. The steering means 1 achieves steering by moving a steering actuator attached to the steering mechanism on the basis of detection results of the swing direction and the swing angle of the operation plate 11. Since the support structure of the operation plate 11 and the structures and operations of the steering angle sensor for detecting the swing angle of the operation plate 11 and the reaction force applying means for applying reaction force to the operation plate 11 are the same as those of the first embodiment shown in FIGS. 1A and 1B, detailed description thereof is omitted.

[0044] With this embodiment wherein the operation plate 11 is disposed on the floor F of the passenger's room under driver's feet, a driver 6 sitting on a seat S can place his feet on right and left end portions of the operation plate 11 and operate the operation plate 11 to swing by applying pressure by stepping on the plate as shown in the figure so as to perform desired steering in respective directions by the swinging operations. Since such a swinging operation of the operation plate 11 is easy and requires a small operation amount in comparison with a turning operation of a steering-wheel-shaped steering means generally used, a load in steering can be decreased and tiredness in driving can be reduced.

[0045] FIG. 6 is a view for showing the sixth embodi-

ment of steering means provided in a steering apparatus for a vehicle according to the present invention. FIG. 7 is a view for showing the seventh embodiment of the same.

[0046] The steering means 1 shown in FIG. 6 is constructed by supporting an operation plate 11 having a large volume at one end of a supporting shaft 10 standing on a floor F of the passenger's room and attaching a seat S, on which a driver is to sit, with the operation plate 11 functioning as a supporting base. The driver sitting on the seat S performs a desired steering in respective directions by making the operation plate 11 swing in accordance with his weight shifted to the right and the left. With such a construction, the driver can steer the vehicle having the same feeling as that of steering a two-wheeled vehicle, a load in steering can be decreased and tiredness in driving can be reduced.

[0047] Neutralization springs 18 are interposed respectively between the right side of the operation plate 11 and the floor F and between the left side of the operation plate 11 and the floor F. The operation plate 11 is constructed to swing right and left against spring force applied by the neutralization springs 18. Since the structures and operations of other portions, such as the support portion of the operation plate 11 and the steering angle sensor 14 for detecting the swing angle of the operation plate 11, are the same as those of the first embodiment shown in FIGS. 1A and 1B, detailed description thereof is omitted.

[0048] Similarly to the steering means 1 shown in FIGS. 4A and 4B, the steering means 1 shown in FIG. 7 is constructed by supporting the operation plate 11 at one end of a supporting shaft (which is not illustrated in the figure) standing on the upper face of the armrest A and fixing a model 19 of a car on the upper face of the operation plate 11. With this structure, a desired steering partly for pleasure can be performed in respective directions by gripping the model 19 of a car and operating the operation plate 11 to swing right and left, so that a load in steering can be decreased and tiredness in driving can be reduced. It should be noted that this figure shows a perspective view of the structure from the front side of the vehicle, i.e., in the opposite direction to FIG. 4A.

[0049] In the structures shown in FIGS. 5 through 7, the operation plate 11 may also be supported so as to swing backward and forward or to be turned on the supporting shaft as well as to swing right and left. In this case, a wide variety of steering forms can be provided using a combination of a swinging operation in backward and forward directions and a swinging operation in right and left directions or a combination of a swinging operation and a turning operation.

[0050] FIG. 8A is an external perspective view for showing the eighth embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention. FIG. 8B is a sectional side view of the steering means. The steering means 2 shown in

these figures is disposed on a part of a dashboard D so as to be displaced by a driver sitting in the passenger's room. As shown in FIG. 8B, the steering means 2 comprises a linear-rod-shaped guiding member 20 extended with the longitudinal direction thereof according with right and left directions, a slider 21 which is retained on the guiding member 20 so as to freely slide in the longitudinal direction and an operation lever (operation member) 22, which is projected toward the driver, having a base supported on the slider 21. A grip 23 is provided on one end of the operation lever 22.

[0051] As shown in FIG. 8B, the slider 21 is biased toward a center portion of the guiding member 20 respectively by a pair of neutralization springs, which are in a resilient contact with both sides of the slider 21, to be positioned at a neutral position where spring forces of these neutralization springs 24 counterbalance each other, i.e., at a longitudinal center position of the guiding member 20. The operation lever 22 constructed in this manner can be shifted in the longitudinal direction of the guiding member 20, i.e. in right and left directions of the vehicle, against spring force applied by the neutralization springs 24 as the slider 21 slides. FIG. 8A illustrates in two dotted dash rules the operation lever 22 which is shifted toward the left side.

[0052] As schematically shown in the figure, a displacement sensor 25 configured as a linear potentiometer detects the displacement position of the operation lever 22 which can be displaced as described above as well as the displacement direction. The detected position is handled as the direction and amount of the operation of the steering means 2 performed for steering and used for controlling an operation of a steering actuator disposed in a steering mechanism which is not illustrated in the figure. The control may be performed in control procedures which are disclosed in Japanese Patent Application Laid-Open No. 10-218000 by the present applicant as control procedures for a steering apparatus of separate type having steering-wheel-shaped steering means.

[0053] In a vehicle provided with the steering means 2 constructed in this manner, a driver who sits on the driver's seat can steer the vehicle by gripping the grip 23 provided at one end of the operation lever 22 which is positioned at the front and displacing the operation lever 22 in right and left directions. Since such a displacement operation of the operation lever 22 is easy and requires a small operation amount in comparison with a turning operation of steering-wheel-shaped steering means generally used, a load in steering can be decreased and tiredness in driving for a long time can be reduced. Furthermore, such a steering apparatus can provide physically handicapped drivers with opportunities of driving.

[0054] Although the above explanation has described a case where the steering means 2 shown in FIGS. 8A and 8B is solely provided, the steering means 2 may be provided, for example, on a pad portion of a steering

wheel which is not illustrated in the figures for assisting the steering-wheel-shaped steering means and used, for example, only for steering at a relatively small angle during a drive on open roads or the like.

[0055] The position where the steering means 2 is disposed is not limited to the dashboard D shown in FIGS. 8A and 8B and the steering means 2 may be disposed in a suitable position, such as on the upper face of the armrest A shown in FIGS. 4A and 4B, as long as the driver can operate the steering means 2.

[0056] FIG. 9A is an external perspective view for showing the ninth embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention and FIG. 9B is a sectional side view of the steering means. FIG. 10A is an external perspective view for showing the tenth embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention and FIG. 10B is a sectional side view of the steering means. The steering means 2 in these figures, similarly to the steering means 2 shown in FIGS. 8A and 8B, comprises a linear-rod-shaped guiding member 20 extended at a part of the dashboard D in the right and left directions, a slider 21 which is retained on the guiding member 20 so as to freely slide in the longitudinal direction and an operation lever (operation member) 22 having a base supported on the slider 21. A grip 23 is provided on one end of the operation lever 22. Since the support structure of the slider 21 at the guiding member 20, the structures and operations of the neutralization springs 24 and the displacement sensor 25 and the contents of the steering control operation based on the position detected by the displacement sensor 25 are the same as those of the eighth embodiment shown in FIGS. 8A and 8B, detailed description thereof is omitted.

[0057] The feature of these embodiments lies in the support structure of the guiding member 20 at the slider 21. The operation lever 22 shown in FIGS. 9A and 9B is inserted into and supported at a sliding bracket 27 provided at the slider 21 so as to slide with respect to the sliding bracket 27 by pushing and pulling operations in the axial direction and to perform a telescopic operation to project from and recede into the slider 21. Such a telescopic operation can be performed between a position illustrated in full lines in FIG. 9A and a position illustrated in one dotted dash rules in the figure. The operation amount is detected by a telescopic motion sensor (which is not illustrated in the figure) interposed between the operation lever 22 and the slider 21.

[0058] With this embodiment, a driver gripping the grip 23 can perform a displacement operation of the operation lever 22 along the guiding member 20 as well as a telescopic operation of the operation lever 22 at respective displacement positions. The detection result of the telescopic motion amount of the operation lever 22 detected by the telescopic motion sensor can be used, for example, for controlling the correspondence between the displacement amount of the operation lever

22 and the movement amount of the steering actuator, or what is called a transfer ratio of steering. In this case, a wide variety of steering forms can be provided including an example wherein a large scale steering is performed by a combination of a push-in operation and a displacement operation of the operation lever 22 while a small scale steering is performed by a combination of a pull-out operation and a displacement operation.

[0059] Moreover, the detection result of the telescopic motion amount detected by the telescopic motion sensor can be used, for example, for controlling increase and decrease of running speed by using the push-in operation as an acceleration operation and the pull-out operation as a brake operation. In this case, approximately the whole of the operations for driving a vehicle can be provided by the combination of displacement operations and telescopic operations of the operation lever 22.

[0060] The operation lever 22 shown in FIGS. 10A and 10B is supported on the upper face of the slider 21 so as to freely swing around a rotational axis 26 and attached to the slider 21 so as to swing in upward and downward directions. The swinging operation amount is detected by a swing angle sensor (which is not illustrated in the figure) provided at the support portion of the operation lever 22.

[0061] With this embodiment, a driver gripping the grip 23 can perform a displacement operation of the operation lever 22 along the guiding member 20 as well as a swinging operation of the operation lever 22 in upward and downward directions at respective displacement positions. The swing angle in upward and downward directions of the operation lever 22 detected by the swing angle sensor can be used, for example, for controlling the correspondence between the displacement amount of the operation lever 22 and the movement amount of the steering actuator, or what is called a transfer ratio of steering. In this case, a wide variety of steering forms can be provided including an example wherein a large scale steering is performed by a combination of an upward swinging operation and a right and left displacement operation of the operation lever 22 while a small scale steering is performed by a combination of a downward swinging operation and a right and left displacement operation.

[0062] Moreover, the detection result of the swing angle in upward and downward directions detected by the swing angle sensor can be used, for example, for controlling increase and decrease of running speed by using the upward swinging operation as an acceleration operation and the downward swinging operation as a brake operation. In this case, approximately the whole of the operations for driving a vehicle can be provided by the combination of right and left displacement operations and upward and downward swinging operations of the operation lever 22. It should be noted that the swing directions of the operation lever 22 are not limited to the upward and downward directions shown in the figure and may be other directions such as right and left

directions.

[0063] FIG. 11 is a view for showing the eleventh embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention. As shown in the figure, the steering means 3 comprises a steering wheel 30 and a left grip 31 and a right grip 32 which are provided respectively at left and right parts of a ring portion of the steering wheel 30.

[0064] The steering wheel 30 is a known steering means which is fixed to one end of a column shaft which is not illustrated in the figure and turned on the axis of the column shaft. The operation amount thereof is detected by a rotational angle detector attached to the column shaft. The detection result is used for controlling an operation of a steering actuator disposed in a steering mechanism which is not illustrated in the figure. The control may be performed in control procedures which are disclosed in Japanese Patent Application Laid-Open No. 10-218000 by the present applicant.

[0065] The left grip 31 and the right grip 32 attached to such a steering wheel 30 are constructed so as to be twisted by a driver gripping them. The twist amount is detected separately by sensors (which are not illustrated in the figure) attached respectively at inner portions thereof. Each detection result is added to a rotation operation amount in the same direction of the steering wheel 30 as a signal indicating the corrective steering amount in the direction and is used for controlling an operation of a steering actuator.

[0066] With this embodiment, the driver can perform steering in right and left directions by turning operations of the steering wheel 30 and perform corrective steering by twisting operations of the left grip 31 and the right grip 32 in this state. Consequently, steering with high accuracy can be easily realized. Moreover, since steering of a small angle to the right or the left can be performed only by a twisting operation of the left grip 31 or the right grip 32, a load in steering can be decreased and tiredness in driving for a long time can be reduced.

[0067] FIG. 12 is a view for showing the twelfth embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention. As shown in this figure, the steering means 3 comprises a rod-shaped steering bar 34 attached to one end of the column shaft 33 so as to cross the column shaft 33 at a right angle and the same left grip 31 and right grip 32 as those of the embodiment shown in FIG. 11 at left and right ends of the steering bar 34.

[0068] The steering bar 34 is a substitute for the steering wheel of the embodiment shown in FIG. 11 and can be turned on the axis of the column shaft 33 within a predetermined angle range. The turning operation amount is detected by a rotational angle detector 35 attached to the column shaft 33. The left grip 31 and the right grip 32 at the ends of the steering bar 34 are constructed so as to be twisted by the driver gripping them. The twisting operation amount is detected separately by sensors attached respectively to inner portions of the

left grip 31 and the right grip 32. Each detection result is, for example, added to a rotation operation amount in the same direction of the steering bar 34 as a signal indicating the corrective steering amount in the direction and the addition result is used for controlling an operation of a steering actuator disposed in a steering mechanism which is not illustrated in the figure.

[0069] With this embodiment, the driver grips the left grip 31 and the right grip 32 at the ends of the steering bar 34 and turns the steering bar 34 right and left by pushing and pulling the respective sides, so as to perform steering according to the operations. The driver further performs a twisting operation of the left grip 31 or the right grip 32 in this state so as to perform a corrective steering of a small angle. Consequently, steering with high accuracy can be easily realized. Moreover, since steering of a small angle to the right or the left can be performed only by a twisting operation of the left grip 31 or the right grip 32, a load in steering can be decreased and tiredness in driving for a long time can be reduced.

[0070] It should be noted that the steering wheel 30 or the steering bar 34 in these embodiments may be fixed so as not to be rotatable so that steering is performed only by a twisting operation of the left grip 31 and the right grip 32. It is also possible to attach pressure sensors 36 and 37 at the left grip 31 and the right grip 32, detect grip force applied to the grips 31 and 32 and perform steering to the left and the right based on the detection result.

[0071] In the structure for detecting grip force applied to the left grip 31 and the right grip 32 as mentioned above, the left grip 31 and the right grip 32 may be provided separately from the steering wheel 30 or the steering bar 34 so that the driver can steer the vehicle by gripping and operating the operation member placed at a suitable position in the passenger's room. With this structure, no limit exists in the driving position of the driver and tiredness in driving can be further reduced.

[0072] FIG. 13 is a view for showing the thirteenth embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention. As shown in this figure, the steering means 4 comprises a steering wheel 40 and a jog dial 41 which is disposed on an upper face of a spoke portion of the steering wheel 40 in proximity to a ring portion.

[0073] The steering wheel 40 is a known steering means which is fixed to one end of a column shaft which is not illustrated in the figure and turned on the axis of the column shaft. The turning operation amount thereof is detected by a rotational angle detector attached to the column shaft. The detection result is used for controlling an operation of a steering actuator disposed in a steering mechanism which is not illustrated in the figure. The control operation is disclosed in Japanese Patent Application Laid-Open No. 10-218000 by the present applicant.

[0074] The jog dial 41 attached to such a steering wheel 40 is constructed so as to be turned on a center

shaft 42 extending in an approximately radial direction of the steering wheel 40 and to be pushed in a radial direction of the center shaft 42. The direction and amount of the rotation operation and existence of the pushing operation are detected by a sensor unit 43 attached to one side of the center shaft 42. Rotation directions of the jog dial 41 are respectively correlated with steering directions to the right and left. The detection result of the rotation amount is, for example, added to the rotation operation amount in the same direction of the steering wheel 40 as signals indicating the corrective operation amount to the respective sides and used for controlling an operation of the steering actuator.

[0075] With this embodiment, the driver can perform steering in right and left directions by turning operations of the steering wheel 40 and perform corrective steering by rotation operations of the jog dial 41 in this state. Consequently, steering with high accuracy can be easily realized. Moreover, since steering of a small angle to the right or the left can be performed only by a rotation operation of the jog dial 41, a load in steering can be decreased and tiredness in driving for a long time can be reduced.

[0076] A pushing operation of the jog dial 41 detected by the sensor unit 43 is used as a signal instructing acceptance and release of the rotation operation of the jog dial 41. In other words, steering or corrective steering by rotation operation of the jog dial 41 requires a pushing operation for the acceptance. Detection results of direction and amount of a rotation operation after the pushing operation of the jog dial 41 are used for steering or corrective steering. Steering performed in this manner is released by another pushing operation. In this manner, it is possible to prevent occurrence of a problem that steering or corrective steering based on unintended operations of the jog dial 41 is performed.

[0077] It should be noted that the steering wheel 40 in this embodiment may be fixed so as not to be rotatable so that steering is performed only by a rotation operation of the jog dial 41. In this case, it is also possible to dispose the jog dial 41 separately from the steering wheel 40 so that the driver can steer the vehicle by performing a rotation operation at a suitable position in the passenger's room. With this structure, no limit exists in the driving position of the driver and tiredness in driving can be further reduced. Furthermore, a dial which cannot accept a pushing operation may be employed in place of the jog dial 41.

[0078] FIG. 14 is a view for showing the fourteenth embodiment of steering means provided in a steering apparatus for a vehicle according to the present invention. As shown in this figure, the steering means 5 is constructed by connecting end portions of an operation member 53, which is configured as a strip-shaped member having a predetermined length, respectively with a pair of supporting rods 51 and 52 projected at both sides of a supporting box 50 so as to form a U-shaped operation portion by the operation member 53 between the

supporting rods 51 and 52. The steering means 5 is disposed at a suitable position in a vehicle which is not illustrated in the figure with the supporting rods 51 and 52 extending in right and left directions.

[0079] A pair of left and right force sensors 54 and 55 for detecting action forces applied to the supporting rods 51 and 52 is disposed in the supporting box 50. When the left half portion of the U-shaped operation member 53 is pulled, the force sensor 54 detects an action force applied to the supporting rod 51 at the same side while when the right half portion of the operation member 53 is pulled, the force sensor 55 detects an action force applied to the supporting rod 52 at the same side. The strengths of the action forces detected in this manner is used as operation amounts in directions corresponding to the respective supporting rods 51 and 52 and used for controlling an operation of a steering actuator disposed in a steering mechanism which is not illustrated in the figure.

[0080] With this embodiment, the driver sits to face the front face of the supporting box 50, grips the middle portions of the U-shaped operation member 53 from right and left sides by his right and left hands and pulls either one of the right and left grip portions so as to perform steering in directions corresponding to the pulling operations. Since steering in the respective directions are performed quantitatively in accordance with the strengths of the operation forces detected at the force sensors 54 and 55, steering amount can be adjusted on the basis of the strength of the pulling operation of a right or left grip portion.

[0081] This embodiment can be structured so as to brake the vehicle when right and left grip portions of the operation member 53 are pulled simultaneously and the force sensors 54 and 55 detect approximately the same action forces. Such a structure can be used for controlling decrease of running speed. Furthermore, this embodiment can be structured so as to accelerate the vehicle when the force sensors 54 and 55 detect periodical force change. Such a structure can also be used for controlling increase of running speed. Such a periodical force change is generated when a "horse-rushing operation" (which is a swing operation to be performed on the reins of the horse when rushing a horse) is performed on the operation member 53. The driver can increase and decrease the vehicle by such a "horse-rushing operation" and a pulling operation. Furthermore, approximately the whole of the operations for driving a vehicle can be provided by a combination of these operations and steering by right and left pulling operations of the operation member 53.

[0082] The operation of the operation member 53 mentioned above is identical with the operation for handling a horse. Consequently, the driver can drive and steer the vehicle with a horse-riding feeling, a load in steering can be decreased and tiredness in driving can be reduced.

[0083] FIG. 15 is an explanatory view for showing a

steering state realizable in a vehicle provided with the aforementioned steering apparatus. As shown in the figure, the driver 6 lies on his back on a reclining seat S wearing a pair of goggles 7 capable of displaying a predetermined image on the inner face of the lenses on so as to perform a predetermined operation while gripping the steering means 8. Displayed on the inner face of the goggles 7 are an image 70 showing the view in front of the vehicle, images 71 and 72 showing a view behind the vehicle and views at the sides of the vehicle and an image 73 displaying meters required for driving operations such as meters indicating a vehicle speed and an engine speed. With this structure, a desired steering can be performed by an operation of the steering means 8 performed by the driver 6 who views these images.

[0084] The steering means 8 shown in FIG. 15 is constructed separately from structure members in the passenger's room, and can be structured by attaching, to an operation box which the driver can grip while lying on the back as shown in FIG. 15, the steering means 1 shown in FIGS. 1A through 7 comprising the operation plate 11 to be operated to swing right and left, steering means 2 shown in FIGS. 8A through 10B comprising the operation lever 22 so as to be displaced right and left, steering means 3 shown in FIGS. 11 and 12 comprising the left and right grips 31 and 32 so as to be twisted or gripped for making operations, or the steering means 4 shown in FIG. 13 comprising a dial, such as the jog dial 41, so as to be rotated.

[0085] As described above in detail, with a steering apparatus for a vehicle according to the present invention which requires a small operation amount and can steer the vehicle by operations of an operation member performed easily, a load in steering can be decreased and tiredness in driving can be reduced. Moreover, such a steering apparatus can provide physically handicapped drivers with opportunities of driving. Furthermore, when the operation member is disposed in a suitable position in the passenger's room, the driver can operate the member in a comfortable position.

Claims

1. A steering apparatus for a vehicle which comprises steering means (1) mechanically separated from a steering mechanism of the vehicle and moves the steering mechanism on the basis of detection results of an operation direction and an operation amount of the steering means (1),
characterized in that the steering means (1) includes:

a plate-shaped or rod-shaped operation member (11) which is supported so as to freely swing with a center portion thereof being fixed; and detecting means (14) for detecting a swing direction and a swing angle of the operation

member (11) respectively as the operation direction and the operation amount.

2. The steering apparatus for a vehicle according to Claim 1, **characterized in that** the steering means (1) further includes:

a first shaft (10a) projected from a part of a body of the vehicle;
a second shaft (10b), which is coupled with the first shaft (10a) so as to be shifted with regard to the first shaft (10a), for supporting the operation member (11); and
a displacement detector (16) for detecting a displacement direction and a displacement amount of the second shaft (10b),

wherein the steering mechanism operates on the basis of the swing direction and the swing angle of the operation member (11) detected by the detecting means (14) and the displacement direction and the displacement amount of the second shaft (10b) detected by the displacement detector (16).

3. The steering apparatus for a vehicle according to Claim 1, **characterized in that** the steering means (1) further includes:

a supporting shaft (10), which is projected from a part of a body of the vehicle, for supporting the operation member (11) so as to be rotated on a center axis thereof and
a rotation detector (17) for detecting a rotation direction and a rotation amount of the operation member (11),

wherein the steering mechanism operates on the basis of the swing direction and the swing angle of the operation member (11) detected by the detecting means (14) and the rotation direction and the rotation amount of the operation member (11) detected by the rotation detector (17).

4. A steering apparatus for a vehicle which comprises steering means (2) mechanically separated from a steering mechanism of the vehicle and moves the steering mechanism on the basis of detection results of an operation direction and an operation amount of the steering means (2),

characterized in that the steering means (2) includes:

an operation member (22) which is supported so as to be freely displaced along a linear displacement pathway; and
detecting means (25) for detecting a displacement direction and a displacement amount of the operation member (22) respectively as the

operation direction and the operation amount.

5. A steering apparatus for a vehicle which comprises steering means (3) mechanically separated from a steering mechanism of the vehicle and moves the steering mechanism on the basis of detection results of an operation direction and an operation amount of the steering means (3),

characterized in that the steering means (3) includes:

a pair of grip members (31, 32) which are arranged in correspondence to operation directions respectively; and
detecting means (36, 37) for detecting strengths of grip forces applied to the grip members (31, 32) as operation amounts in the operation directions corresponding to the respective grip members.

6. A steering apparatus for a vehicle which comprises steering means (4) mechanically separated from a steering mechanism of the vehicle and moves the steering mechanism on the basis of detection results of an operation direction and an operation amount of the steering means (4),

characterized in that the steering means (4) includes:

a dial (41) which is supported so as to be rotated on a center axis thereof and
detecting means (43) for detecting a rotation direction and a rotation amount of the dial (41) respectively as the operation direction and the operation amount.

7. A steering apparatus for a vehicle which comprises steering means (5) mechanically separated from a steering mechanism of the vehicle and moves the steering mechanism on the basis of detection results of an operation direction and an operation amount of the steering means (5),

characterized in that the steering means (5) includes:

an operation member (53) formed of a strip-shaped member having end portions supported separately and a U-shaped operation portion between the supported end portions; and
detecting means (54, 55) for detecting forces, which are applied to the supported end portions by a pulling operation of the operation member (53), as operation amounts in directions corresponding to the respective supported end portions.

FIG. 1A




FIG. 1B




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6




FIG. 7




FIG. 8A




FIG. 8B




FIG. 9A




FIG. 9B




FIG. 10A




FIG. 10B




FIG. 11




FIG. 12




FIG. 13




FIG. 14





FIG. 15





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 03 00 7201

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	DE 196 21 023 C (DAIMLER BENZ AG) 18 September 1997 (1997-09-18)	1-4	B62D1/12
Y	* column 1, line 40 - line 45 * * column 2, line 25 - line 47 * * column 2, line 64 - column 3, line 21 * * column 3, line 2 - line 21 * * column 3, line 50 - column 4, line 6; claims 1,2,7; figures 1-4 *	5,6	
A	---	7	
X	WO 88 09279 A (SAAB SCANIA AB) 1 December 1988 (1988-12-01)	1-4	
A	* page 3, line 1 - line 11 * * page 4, line 14 - line 26 * * page 4, line 33 - page 5, line 9 * * page 9, line 7 - line 19 * * page 10, line 1 - line 14 * * page 11, line 5 - line 15 * * page 20, line 3 - line 11; claims 1,6; figures 1-9,14 *	5-7	TECHNICAL FIELDS SEARCHED (Int.Cl.7) B62D
Y	US 3 312 123 A (RUMPF ROBERT J) 4 April 1967 (1967-04-04) * column 1, line 70 - column 2, line 13 * * column 3, line 11 - line 35 * * column 4, line 41 - line 50; claims 1,2; figures 1-4 *	6	
X	US 4 646 869 A (KERNER JR HADYN H) 3 March 1987 (1987-03-03) * column 1, line 44 - line 63 * * column 2, line 40 - line 50 * * column 3, line 18 - line 41; figures 2,4 * --- -/--	7	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 3 July 2003	Examiner Tiedemann, D
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03/82 (P4/C01)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 03 00 7201

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
Y	WO 01 76932 A (NERVO AURELIO ;HOLWEG EDUARDUS GERARDUS MARIA (NL); KAPAAN HANDRIK) 18 October 2001 (2001-10-18) * page 1, line 21 - page 2, line 18 * * page 3, line 17 - line 30; claim 1; figures 1,2 *	5	
X,P	PATENT ABSTRACTS OF JAPAN vol. 2002, no. 10, 10 October 2002 (2002-10-10) & JP 2002 160642 A (HONDA MOTOR CO LTD), 4 June 2002 (2002-06-04) * abstract *	1,3	
X	EP 1 065 130 A (STILL WAGNER GMBH & CO KG) 6 3 January 2001 (2001-01-03) * column 1, line 44 - line 63 * * column 2, line 40 - line 50 * * column 3, line 18 - line 41; claims 1,4; figures 2,4 *	6	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 3 July 2003	Examiner Tiedemann, D
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 03 00 7201

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

03-07-2003

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 19621023	C	18-09-1997	DE 19621023 C1	18-09-1997
WO 8809279	A	01-12-1988	WO 8809279 A1	01-12-1988
US 3312123	A	04-04-1967	GB 1073861 A	28-06-1967
US 4646869	A	03-03-1987	NONE	
WO 0176932	A	18-10-2001	NL 1014912 C2	12-10-2001
			AU 5065401 A	23-10-2001
			EP 1272384 A1	08-01-2003
			WO 0176932 A1	18-10-2001
JP 2002160642	A	04-06-2002	DE 10157944 A1	04-07-2002
			US 2002063015 A1	30-05-2002
EP 1065130	A	03-01-2001	DE 19929797 A1	04-01-2001
			EP 1065130 A2	03-01-2001

EPC FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

PUB-NO: EP001350706A1
DOCUMENT-IDENTIFIER: EP 1350706 A1
TITLE: Steering apparatus for vehicle
PUBN-DATE: October 8, 2003

INVENTOR-INFORMATION:

NAME	COUNTRY
HIGASHI, MASAYASU	JP
MAEDA, SHINGO	JP
SEGAWA, MASAYA	JP
KIMURA, SHUJI	JP
HAYAMA, RYOUHEI	JP
KADA, TOMOYASU	JP

ASSIGNEE-INFORMATION:

NAME	COUNTRY
KOYO SEIKO CO	JP

APPL-NO: EP03007201
APPL-DATE: March 29, 2003

PRIORITY-DATA: JP2002099170A (April 1, 2002)

INT-CL (IPC): B62D001/12

EUR-CL (EPC): B62D001/02 , B62D001/12

ABSTRACT:

CHG DATE=20031203 STATUS=O>The steering means 1 is constructed by supporting a center portion of a rectangle-plate-shaped operation plate

11 at one end of a supporting shaft 10 projected from the front face of a dashboard D so as to freely swing in right and left directions. A steering apparatus for a vehicle having the steering means 1 detects the swing direction and the swing angle of the operation plate 11 with a steering angle sensor 14 provided at a support portion and moves a steering mechanism in the detected direction in accordance with the detected angle so as to steer the vehicle. With this structure, a load in steering can be decreased and tiredness in driving can be reduced. Furthermore, such a steering apparatus can realize steering means which physically handicapped drivers can operate easily.